

MS52-R RS232

High Speed 2D/1D Area Imager



CARATTERISTICHE

LIGHT SOURCE: Puntatore LED bianco da 617 nm
SCAN DISTANCE: da 40 a 600 mm
SCAN TYPE: Image Cmos
RESOLUTION: 5 mil

SYMBOLOGIES

1D: UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 Full ASCII, Codabar(NW7), Code 128, EAN 128 Interleaved 2/5, Code 93, Addendum 2 of 5, IATA Code Standard 2/5, MSI/Plessey, China Postal Code, Code 32, RSS 14, RSS 14, RSS Limited, RSS Expanded

2D: QR Code/DM10mil, Maxicode, Data Matrix, PDF417(standard), MicroPDF417

CARATTERISTICHE GENERALI

POWER SUPPLY: 5V DC / 170 mAh
CABLE: USB, 180 cm
SCAN INDICATOR: Led, Buzzer
IP54
FALL TEST: 2 m

INTERFACCIA

RS232, RS485 Optional

MISURE

PROFONDITA': 94 mm
LUNGHEZZA: 67 mm
ALTEZZA: 173 mm
PESO: 220 g



Ticketing



Supermarket



Lottery



Retail